



- Excellent adhesion
- Permanently flexible
- Extrudes from -20°F to 160°F
- Adheres to:
  - Vinyl Siding
  - Fiber Cement Siding
  - Metals
  - Wood
  - Masonry
  - PVC
  - PVDF
  - Common Construction Materials

MX150 Translucent	MR101 Bright White	MR3010 Colonial White, Snow White, 280 White	MX145 Sandstone Beige, Pearl	MR105 Bone Linen	MX143 Heritage Cream, Wheat
MX108 Autumn Yellow	MR3401 Almond	MR3482 Silver Ash	MX3546 Herringbone	MR3561 Silver Grey	MR3461 Light Maple, Desert Tan, Desert Sand
MX3473 Saddle	MR3404 Green Tea	MX3455 Sand NX	MX3405 Sandpiper	MX3503 Glacier Blend	MX3344 Linen
MR115 Sterling Gray, Pearl Gray	MR3412 Buckskin	MR138 Savannah Wicker, Rye	MR156 Seagrass	MX3302 Natural Clay, Cypress	MX3324 Suede
MX3301 Pebblestone Clay	MR3500 Granite Gray, Greystone, Harbor Grey	MX141 Rugged Canyon	MX112 Charcoal Gray, Deep Granite	MR3702 Forest	MR3510 Flagstone
MX3290 Mountain Cedar	MR157 Terra Cotta	MR155 Hearthstone	MR3801 Pacific Blue	MR3823 Regatta	MR134 Sable Brown, Terra Bronze, Montana Suede
MX3570 Tuxedo Gray	MX3901 Lighthouse Red	MR182 Autumn Red	MR169 Grecian Green	MR137 Royal Brown	MR120 Musket Brown, Musket Brown C & A
MR121 AMP Dark Bronze	MX3206 Dark Bronze	MR110 Black			

We recommend MX150 Translucent for colors Bermuda Blue, Harbor Blue, Oxford Blue, Portsmouth Blue, Spruce, Ivy Green, Quiet Willow, Tuscan Olive, & Victorian Gray.

Colors shown for illustrative purposes. Verify product color match before applying.

## Multi-Purpose Adhesive Sealant Metal Roof & Panel Adhesive Sealant



Metal Roof & Panel  
 Adhesive Sealant

Multi-Purpose  
 Adhesive Sealant

Gutter Seal  
 (paste & flowable)

Hybrid  
 Construction Sealant

Textured Hybrid  
 Construction Sealant

Tub Surround Sealant  
 & Tile Grout

Expansion Joint  
 Sealant

Pitch Pocket  
 Penetration Sealant

Fibered Roof Mastic

Butter Grade Mastic

Metal Roof Repair  
 & Patch Mastic

**NOVAGARD**

5109 Hamilton Avenue, Cleveland, OH 44114 USA  
 (216) 881-8111 | (800) 380-0138 | (216) 881-6977 F  
 novagard.com

ISO 9001:2015 QMS (with Design), IATF 16949:2016 QMS (with Design)  
 Certified Women's Business Enterprise

PRODUCT SPECIFICATIONS			
Physical Property	Test Method	Performance Range Type I - Class 35	Performance Range Type II - Class 50
Appearance		Paste (Various Colors)	Paste (Various Colors)
Viscosity	Brookfield #7 @10 rpm	3,500 - 7,000 poises	4,500 - 8,000 poises
Extrusion Rate	1/8" Orifice @ 50 psi	30 - 80 grams/minute	30 - 80 grams/minute
Skin Over Time	3/8" @ 50% RH & 77°F	5 - 10 minutes	5 - 10 minutes
Through Cure	3/8" @ 50% RH & 77°F	48 hours (14 days for OEM window applications)	48 hours (14 days for OEM window applications)

TYPICAL PROPERTIES*			
Physical Property	Test Method	Typical Value Type I - Class 35	Typical Value Type II - Class 50
Specific Gravity		1.00 - 1.05	1.15 - 1.25
Tensile Strength	ASTM D412	140 - 200 psi	170 - 220 psi
Elongation	ASTM D412	500 - 650%	800 - 1,000%
Tear Resistance	ASTM D624	30 - 35 pli	30 - 35 pli
Shore A Hardness	ASTM D2240	20 +/- 5	25 +/- 5
Service Temperature		-40°F to 400°F (-40°C to 204°C)	-40°F to 400°F (-40°C to 204°C)
Joint Sealant Designation	ASTM C920	Type S Grade NS Class 35 Use NT, M, G, A, O	Type S Grade NS Class 50 Use NT, M, G, A, O
Adhesion Glass Aluminum Vinyl	ASTM D903	12 - 15 pli 10 - 14 pli 12 - 15 pli	12 - 15 pli 10 - 14 pli 12 - 15 pli

\*The values outlined reflect testing that was conducted under laboratory conditions, actual results may vary. The information provided in the above table is not intended for use in preparing specifications. Please consult manufacturer for additional information.

### Permanently Flexible

- Will not shrink or crack
- Waterproof
- Mold/Mildew resistant
- Superior UV resistance

### Interior and Exterior Applications

- Excellent adhesion to most building substrates
- Completely cured within 48 hours
- Will not sag or slump
- Tack-free in 10 minutes

### Easily Gunned at all Temperatures

- Weatherproof plastic cartridges with removable tips
- Excellent tooling properties

### VOC Compliant in all 50 States (Green Building Compliant)

- Low odor
- Solvent free

### AAMA Verified for Window Installs

- Will not freeze
- Available in all major siding, trim coil, window, and metal roof manufacturer colors
- 18 month shelf life

### Professional Grade



Proudly made in Cleveland, OH  
 Effective Date: Jul 2023-v1.2