



- Excellent adhesion
- Permanently flexible
- Extrudes from -10°F to 160°F
- Adheres to:
 - Metals
 - Wood
 - Masonry
 - PVC
 - PVDF
 - Asphalt Shingles
 - Common Construction Materials

NOVABOND

Hybrid Construction Sealant




NBP105
Natural White



NBP107
Antique Ivory




NBP3515
Seaside Grey




NBP3433
Misty Taupe




NBP3433
Willow



NBP3432
Chestnut




NBP3526
Slate




NBP3810
Harbor Blue




NBP3752
Spanish Moss




NBP3533
Flagstone




NBP3811
Blue Spruce




NBP182
Cabernet Red



NBP3527
Storm Grey



NBP3431
Sand Dune



NBP3231
Saddle Wood

NOVABOND

Hybrid Construction Sealant



**Metal Roof & Panel
Adhesive Sealant**

**Multi-Purpose
Adhesive Sealant**

**Gutter Seal
(paste & semi-self leveling)**

**Hybrid
Construction Sealant**

**Textured Hybrid
Construction Sealant**

**Tub Sealant
& Pool Tile Grout**

**Expansion Joint
Sealant**

**Pitch Pocket
Penetration Sealant**

Fibered Roof Mastic

Butter Grade Mastic

**Metal Roof Repair
& Patch Mastic**

NOVAGARD®

5109 Hamilton Avenue, Cleveland, OH 44114 USA
(216) 881-8111 | (800) 380-0138 | (216) 881-6977 F
novagard.com

ISO 9001:2015 QMS (with Design), IATF 16949:2016 QMS (with Design)
Certified Women's Business Enterprise

PRODUCT SPECIFICATIONS		
Physical Property	Test Method	Performance Range
Appearance		Paste (Various Colors)
Viscosity	Brookfield #7 @ 10 rpm	≥ 3,000 poises
Extrusion Rate	1/8" Orifice @ 50 psi	≥ 50 grams/minute
Skin Over Time	3/8" @ 50% RH & 77°F	10-45 Minutes
Through Cure	3/8" @ 50% RH & 77°F	7 days

TYPICAL PROPERTIES*		
Physical Property	Test Method	Typical Value
Specific Gravity		1.40- 1.50
Tensile Strength	ASTM D412	200 psi
Elongation	ASTM D412	300%
Hardness (Shore A)	ASTM D2240	45 ± 5
Adhesion Glass Aluminum Wood PVC	ASTM D903	13 pli 15 pli 15 pli 14 pli
Joint Movement	ASTM C719	± 35
UV Exposure	ASTM G154 (2,000 hours UV-A)	Pass
Shelf Life	-	12 months

*The values outlined reflect testing that was conducted under laboratory conditions, actual results may vary. The information provided in the above table is not intended for use in preparing specifications. Please consult manufacturer for additional info.

Paintable in 1 Hour

- Permanently flexible
- Will not shrink or crack
- Waterproof
- Mold/Mildew resistant
- UV resistant

Interior and Exterior Applications

- Excellent adhesion to most building substrates
- Completely cured within 5-7 days
- Will not sag or slump
- Tack-free in 10-45 minutes

Easily Gunned at all Temperatures

- Weatherproof plastic cartridges with removable tips
- Excellent tooling properties

VOC Compliant in all 50 States (Green Building Compliant)

- California Proposition 65 Compliant
- Low odor
- Solvent free

AAMA Verified for Window Installs (smooth paste)

- Available in all major siding, trim coil, and window manufacturer colors
- Will not freeze

Professional Grade



NovaBond is proudly
made in Cleveland, OH
Effective Date: Feb 2024-v1.6