


NOVABOND

Hybrid Construction Sealant



Meets or exceeds all
HardiePlank ColorPlus®
Requirements

- Exceeds ASTM C920, Grade NS
- 15 year sealant warranty (matches Hardie ColorPlus® warranty)
- Class 35
- Excellent toolability
- Excellent adhesion
- Permanently flexible
- Paintable in 1 hour
- Extrudes down to -10°F
- Adheres to:
 - Fiber Cement
 - Metal
 - Wood
 - Masonry
 - PVC
 - PVDF
 - Asphalt Shingles
 - Vinyl
 - Common Construction Materials



NBP100
Prime & Paint



NBP3020
Arctic White



NBP3021
Sail Cloth



NBP3434
Navajo Beige




NBP3610
Woodland Cream



NBP3615
Embellished Cream
(Wawa)



NBP3431
Cobble Stone




NBP3532
Pearl Gray



NBP3436
Sandstone Beige



NBP3430
Autumn Tan



NBP3531
Light Mist



NBP3433
Monterey Taupe



NBP3432
Khaki Brown



NBP3753
Heathered Moss



NBP3752
Mountain Sage



NBP3242
Woodstock Brown



NBP3241
Timber Bark




NBP3810
Boothbay Blue




NBP3811
Evening Blue



NBP3812
Deep Ocean




NBP3533
Night Gray



NBP3526
Gray Slate



NBP3243
Chestnut Brown




NBP3940
Countrylane Red



NBP3231
Rich Espresso



NBP3527
Iron Gray



NBP3525
Aged Pewter



NBP110
Midnight Black

15 year warranty available for Hardie Plank ColorPlus® installations.

Colors shown for illustrative purposes. Verify product color match before applying.
Trademarks are the property of trademark holder(s).



**Meets or exceeds all
HardiePlank ColorPlus®
Requirements**

- Exceeds ASTM C920, Grade NS
- 15 year sealant warranty (matches Hardie ColorPlus® warranty)
- Class 35
- Excellent toolability
- Excellent adhesion
- Permanently flexible
- Paintable in 1 hour
- Extrudes down to -10°F
- Adheres to:
 - Fiber Cement
 - Metal
 - Wood
 - Masonry
 - PVC
 - PVDF
 - Asphalt Shingles
 - Vinyl
 - Common Construction Materials

NOVABOND

Hybrid Construction Sealant

Product Specifications

| Physical Property | Test Method | Smooth Performance Range |
|-------------------|------------------------|---------------------------|
| Appearance | | Paste (Various Colors) |
| Viscosity | Brookfield #7 @ 10 rpm | ≥ 3,000 poises |
| Extrusion Rate | 1/8" Orifice @ 50 psi | ≥ 50 grams/minute |
| Skin Over Time | 3/8" @ 50% RH & 77°F | 10-45 Minutes |
| Through Cure | 3/8" @ 50% RH & 77°F | 7 days |

Typical Properties*

| Physical Property | Test Method | Smooth Typical Value |
|-------------------|---------------------------------|----------------------|
| Specific Gravity | | 1.40- 1.50 |
| Tensile Strength | ASTM D412 | 200 psi |
| Elongation | ASTM D412 | 400% |
| Shore Hardness | ASTM D2240 | 40+/- 5 |
| Adhesion | | |
| Glass | | 13 pli |
| Aluminum | ASTM D903 | 15 pli |
| Wood | | 15 pli |
| PVC | | 14 pli |
| Joint Movement | ASTM C719 | +/- 35 |
| UV Exposure | ASTM G154 (2,000 hours UV-A) | Pass |
| Shelf Life | - | 18 months |

*The values outlined reflect testing that was conducted under laboratory conditions, actual results may vary. The information provided in the above table is not intended for use in preparing specifications. Please consult manufacturer for additional info.

Paintable in 1 Hour

- Permanently flexible
- Will not shrink or crack
- Waterproof
- Mold/Mildew resistant
- UV resistant

Interior and Exterior Applications

- Excellent adhesion to most building substrates
- Completely cured within 5-7 days
- Will not sag or slump
- Tack-free in 10-45 minutes

Easily Gunned at all Temperatures

- Weatherproof plastic cartridges with removable tips
- Excellent tooling properties

VOC Compliant in all 50 States (Green Building Compliant)

- California Proposition 65 Compliant
- Low odor
- Solvent free

AAMA Verified for Window Installs (smooth paste)

- Available in all major siding, trim coil, and window manufacturer colors
- Will not freeze

Professional Grade

NOVAGARD

5109 Hamilton Avenue, Cleveland, OH 44114 USA
(216) 881-8111 | (800) 380-0138 | (216) 881-6977 F
novagard.com

ISO 9001:2015 QMS (with Design), IATF 16949:2016 QMS (with Design)
Certified Women's Business Enterprise



NovaBond is proudly made in Cleveland, OH
Effective Date: Nov 2022-v2.4