



- Excellent adhesion
- Permanently flexible
- Extrudes to -20°F
- Adheres to:
 - Metals
 - Wood
 - Masonry
 - PVC
 - PVDF
 - Common Construction Materials

NOVAFLEX


Multi-Purpose Adhesive Sealant



DESERT
STONE
MX3461




TERRA
BROWN
MX3333



QUARRY
GRAY
MX111



PRAIRIE
CLAY
MX3302




REDWOOD
RED
MX3901



MARSHLAND
MOSS
MX150



TIMBERLAND
SUEDE
MX141



CAVERN
STEEL
MX117



TUNDRA
GRAY
MX117



SUMMIT
BLUE
MX177



CANYON
BROWN
MX132



ABYSS
BLACK
MX110




- Neutral cure silicone
- Excellent adhesion
- Permanently flexible
- Extrudes to -20°F
- Adheres to:
 - Metals
 - Wood
 - Masonry
 - PVC/PVDF
 - Common Construction Materials
- Also used as
 - Gutter Sealant
 - Chimney Flashing
 - Snow Guard
 - Pipe Boots

NOVAFLEX


Metal Roof Adhesive Sealant



SNOWSCAPE
WHITE
MR3010



SHORELINE
CREAM
MR3401



SAND
DUNES
MR3401



RAPIDS
BLUE
MR178

Colors shown for illustrative purposes. Verify product color match before applying.
We recommend our Translucent MR150 to be paired with Marshland Moss listed above.

Made in USA. Professional Grade.

Product Specifications

Physical Property	Test Method	Metal Roof Adhesive Sealant		Multi-Purpose Adhesive Sealant	
		Performance Range Type I - Class 35	Performance Range Type II - Class 50	Performance Range Type I - Class 35	Performance Range Type II - Class 50
Appearance		Paste (Various Colors)	Paste (Various Colors)	Paste (Various Colors)	Paste (Various Colors)
Viscosity	Brookfield #7 @ 10 rpm	3,500-7,000 poises	4,500-8,000 poises	3,500-7,000 poises	4,500-8,000 poises
Extrusion Rate	1/8" Orifice @ 50 psi	30 - 80 grams/minute	30 - 80 grams/minute	30 - 80 grams/minute	30 - 80 grams/minute
Skin Over Time	3/8" @ 50% RH & 77°F	5 - 10 minutes	5 - 10 minutes	5 - 10 minutes	5 - 10 minutes
Through Cure	3/8" @ 50% RH & 77°F	48 hours (14 days for OEM window applications)	48 hours (14 days for OEM window applications)	48 hours (14 days for OEM window applications)	48 hours (14 days for OEM window applications)

Typical Properties*

Physical Property	Test Method	Metal Roof Adhesive Sealant		Multi-Purpose Adhesive Sealant	
		Typical Value Type I - Class 35	Typical Value Type II - Class 50	Typical Value Type I - Class 35	Typical Value Type II - Class 50
Specific Gravity		1.00 - 1.05	1.15 - 1.25	1.00 - 1.05	1.15 - 1.25
Tensile Strength	ASTM D412	140 - 200 psi	170 - 220 psi	140 - 200 psi	170 - 220 psi
Elongation	ASTM D412	500 - 650%	800 - 1000%	500 - 650%	800 - 1000%
Tear Resistance	ASTM D624	30 - 35 pli	30 - 35 pli	30 - 35 pli	30 - 35 pli
Shore Hardness	ASTM D2240	20 +/- 5	25 +/- 5	20 +/- 5	25 +/- 5
Service Temperature		- 40°F to 400°F (- 40°C to 204°C)	- 40°F to 400°F (- 40°C to 204°C)	- 40°F to 400°F (- 40°C to 204°C)	- 40°F to 400°F (- 40°C to 204°C)
Joint Sealant Designation	ASTM C920	Type S Grade NS Class 35 Use NT, M, G, A, O	Type S Grade NS Class 50 Use NT, M, G, A, O	Type S Grade NS Class 35 Use NT, M, G, A, O	Type S Grade NS Class 50 Use NT, M, G, A, O
Adhesion Glass Aluminum Vinyl	ASTM D903	12 - 15 pli 10 - 14 pli 12 - 15 pli	12 - 15 pli 10 - 14 pli 12 - 15 pli	12 - 15 pli 10 - 14 pli 12 - 15 pli	12 - 15 pli 10 - 14 pli 12 - 15 pli

* The values outlined reflect testing that was conducted under laboratory conditions, actual results may vary. The information provided in the above table is not intended for use in preparing specifications. Please consult manufacturer for additional information.

Permanently Flexible

- Will not shrink or crack
- Mold/Mildew resistant
- Waterproof
- Superior UV resistance

Interior and Exterior Applications

- Excellent adhesion to most building substrates
- Will not sag or slump
- Tack-free in 10 minutes
- Completely cured within 48 hours

Easily Gunned at all Temperatures

- Weatherproof plastic cartridges with removable tips
- Excellent tooling properties

VOC Compliant in all 50 States (Green Building Compliant)

- Low odor
- Solvent free

AAMA Verified for Window Installs

- Will not freeze
- 18 month shelf life
- Available in all major siding, trim coil, window, and metal roof manufacturer colors

Professional Grade