



Permanently flexible

Paintable in 1 hour

Interior and exterior sealing

- Safe to use indoors
- Excellent tooling and weathering properties
- Applies vertically & overhead
- Superior adhesion
- Extrudes from -10°F to 160°F
- Adheres to:
 - metal
 - wood
 - masonry
 - PVC
 - PVDF
 - Asphalt shingles
 - most common construction materials

VOC compliant in all 50 states (Green Building Compliant)

- PFAS free
- Low odor
- Solvent free
- HFC free

Easily gunned at all temperatures

- Weatherproof plastic cartridges w/removable tips
- Excellent tooling properties
- Will not freeze

Available in

- 10 oz cartridges
- 20 oz sausages
- 55 gallon drums

NOVABOND

Hybrid Construction Sealant


Stock Colors



NBP100
White



NBP105
Antique White



NBP107
Canvas




NBP145
Canvas




NBP140
Beige




NBP3431
Cobblestone



NBP146
Sandstone



NBP134
Terratone



NBP120
Dark Bronze



NBP110
Black


Made to Order Colors




NBP3020
Arctic White




NBP3515
Cape Cod Gray




NBP159
Limestone




NBP182
Red Rock



NBP193
Cocoa Bean



NBP168
Forest Green



NBP194
Exterior Bronze

NOVABOND^{TX}

Textured Hybrid Construction Sealant

Also available in a textured formula to complement mortar, brick, stone, concrete, asphalt, and stucco applications.



Available in white

We also offer Made to Order colors to match popular mortars: Beige, Limestone, Cobblestone, Cape Cod Gray, Dark Bronze, and Black. Contact your sales rep for order information and program details.



Visit novagard.com/colors to use our online matching tool to cross reference NovaFlex colors to popular manufacturers.

NOVABOND

Hybrid Construction Sealant

Textured Hybrid Construction Sealant



PRODUCT SPECIFICATIONS			
Physical Property	Test Method	Smooth Performance Range	TXtUre Performance Range
Appearance		Paste (Various Colors)	Textured Paste (Various Colors)
Viscosity	Brookfield #7 @ 10 rpm	≥ 3,000 poises	Thixotropic Paste
Extrusion Rate	1/8" Orifice @ 50 psi	≥ 50 grams/minute	Gunable
Skin Over Time	3/8" @ 50% RH & 77°F	10-45 minutes	15-45 minutes
Through Cure	3/8" @ 50% RH & 77°F	7 days	7 days

TYPICAL PROPERTIES *			
Physical Property	Test Method	Smooth Typical Value	TXtUre Typical Value
Specific Gravity		1.40 - 1.50	1.40 - 1.50
Tensile Strength	ASTM D412	200 psi	220 psi
Elongation	ASTM D412	300%	200%
Hardness (Shore A)	ASTM D2240	45+/- 5	45+/- 5
Service Temperature		-30°F to 200°F (-34°C to 93°C)	-30°F to 200°F (-34°C to 93°C)
Application Temperature		-10°F to 160°F (-23°C to 71°C)	-10°F to 160°F (-23°C to 71°C)
Adhesion Glass Aluminum Wood PVC	ASTM D903	13 pli 15 pli 15 pli 14 pli	- 15 pli 15 pli 14 pli
Joint Movement	ASTM C719	+/- 35	+/- 25
UV Exposure	ASTM G154 (2,000 hours UV-A)	Pass	Pass

*The values outlined reflect testing that was conducted under laboratory conditions, actual results may vary. The information provided in the above table is not intended for use in preparing specifications. Please consult manufacturer for additional info.

Paintable in 1 Hour

- Permanently flexible
- UV resistant
- Waterproof
- Mold/Mildew resistant
- Resists dirt pickup
- Long lasting with zero shrinkage or cracking

Interior and Exterior Applications

- Excellent adhesion to most building substrates
- Completely cured within 5-7 days
- Will not sag or slump
- Tack-free in 10-45 minutes

AAMA Verified for Window Installs (smooth paste)

- available in many major window manufacturer, siding, and trim coil colors

Novagard offers a complete line of **installation sealants**

Multi-Purpose Adhesive Sealant

Metal Roof & Panel Adhesive Sealant

Gutter Seal (paste & semi-self leveling)

Hybrid Construction Sealant

Textured Hybrid Construction Sealant

Silicone Tub Sealant & Pool Tile Grout

Silicone Tub and Tile Adhesive

Expansion Joint Sealant

Pitch Pocket Penetration Sealant

Fibered Roof Mastic

Butter Grade Mastic

Metal Roof Repair & Patch Mastic



NOVAGARD

5109 Hamilton Avenue
Cleveland, OH 44114 USA
(216) 881-8111 | (800) 380-0138
novagard.com