



NOVAFLEX[®] SILICONE

Gutter PLUS

NovaFlex Gutter Plus Premium Silicone Adhesive Sealant is the ultimate waterproofing solution. Gutter Plus creates a durable, flexible seal that won't crack, shrink, or degrade over time. Ideal for metal, vinyl, and wood surfaces, it bonds quickly to seal joints, seams, and small gaps, and is perfect for preventing leaks in any season.

- **100% neutral cure silicone**
- **UV stable**
- **Excellent adhesion to most common construction materials**
- **Extrudes from -20°F to 160°F**
- **Mold/mildew resistant**
- **All weather formula**
- **Solvent free**

Applications: Sealing gutter seams and end caps, underdeck panel joints, edge flashings, downspout connections and drain elbows, vents, rain carrying systems, and small roof repairs. Field glazing.

Packaging: 10 oz cartridges

Colors: Translucent, gray, white



NOVAGARD[®]
Performance Silicones



NOVAFLEX[®] SILICONE

Selecting the right sealant

Formulation	SILICONE	TRIPOLYMER	SOLVENT
Tack free time	5 – 10 minutes	15 minutes	30 minutes
Through cure time	2 days (3/8" bead)	5 days	7 – 14 days
Shrinkage after cure	Undetectable (99% solids)	Significant (under 60% solids)	Significant (70% solids)
VOC compliant	All 50 states	Cannot be sold in California	Cannot be sold in California
UV Resistance	Excellent	Good	Good
Weatherability	Excellent	Good	Good
Service temp.	-40°F to 400°F	-40°F to 180°F	0°F to 150°F
Application temp.	-20°F to 160°F	0°F to 140°F	40°F to 120°F
Tensile strength	200 – 250 psi	140 psi	not available
Elongation	400 – 450%	900%	not available
Clean up	Wipes clean with damp rag	Requires solvents and scraping	Requires mineral spirits or paint thinner
Adheres to	Vinyl, wood, masonry, steel, brick, ceramics, glass, fiberglass, stone, concrete, aluminum, and building paper	Asphalt shingles, masonry, glass, concrete, vinyl, sheet metal, wood, and other common building substrates	Aluminum, galvanized steel, and vinyl

NOVAGARD[®]
Performance Silicones