

# NOVAFLEX<sup>®</sup> SILICONE

## Gutter Sealant

NovaFlex Gutter Sealant is a non-corrosive, low odor silicone sealant that cures to a flexible, durable, rubber like solid. The non-sag formula is recommended for the assembly, repair, and sealing of gutters. It functions both as an adhesive and a sealant, bonding to most common substrates without the need for a primer.

- **Rain safe in 1 hour**
- **Completely cured in 24-30 hours**  
(depending on temperature, humidity & thickness)
- **Extrudes from -20°F to 160°F**
- **UV and mold/mildew resistant**
- **Permanently flexible**
- **All weather formula**
- **Solvent free**

**Applications:** gutters, under decks, patio covers, carports, and water carrying systems

**Packaging:** 10 oz cartridges, 3 oz squeeze tubes

**Color:** gray



**NOVAGARD<sup>®</sup>**  
Performance Silicones



# NOVA FLEX SILICONE

## Selecting the right sealant

	SILICONE	TRIPOLYMER	SOLVENT
Formulation	<b>SILICONE</b>	<b>TRIPOLYMER</b>	<b>SOLVENT</b>
Tack free time	<1 hour	15 minutes	30 minutes
Through cure time	24 - 30 hours	5 days	7 - 14 days
Shrinkage after cure	Undetectable (99% solids)	Significant (under 60% solids)	Significant (70% solids)
VOC compliant	All 50 states	Cannot be sold in California	Cannot be sold in California
UV Resistance	Excellent	Good	Good
Weatherability	Excellent	Good	Good
Service temp.	-40°F to 400°F	-40°F to 180°F	0°F to 150°F
Application temp.	-20°F to 160°F	0°F to 140°F	40°F to 120°F
Tensile strength	150 - 300 psi	140 psi	not available
Elongation	400 - 950%	900%	not available
Clean up	Wipes clean with damp rag	Requires solvents and scraping	Requires mineral spirits or paint thinner
Adheres to	Vinyl, wood, masonry, steel, brick, ceramics, glass, fiberglass, stone, concrete, aluminum, and building paper	Asphalt shingles, masonry, glass, concrete, vinyl, sheet metal, wood, and other common building substrates	Aluminum, galvanized steel, and vinyl