

# Novagard Solutions™

## MATERIAL SAFETY DATA SHEET

### SECTION 1- CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** RTV 400-116

**GENERIC DESCRIPTION:** Silicone Elastomers

**MANUFACTURED BY:** **Novagard Solutions™**  
5109 Hamilton Avenue  
Cleveland, OH 44114 216-881-8111  
[www.Novagard.com](http://www.Novagard.com)

**EMERGENCY PHONE NUMBER:** CHEMTREC 800-424-9300 (24 hour)

**REVISED:** 06-29-09 **PREPARED BY:** Brian Chambers

### SECTION 2 - HAZARDOUS COMPONENTS

| COMPONENT                  | CAS No.    | WT %  | OSHA-PEL             |      | ACGIH-TLV            |        |
|----------------------------|------------|-------|----------------------|------|----------------------|--------|
|                            |            |       | TWA                  | STEL | TWA                  | STEL   |
| Silica, amorphous          | 68611-44-9 | 0-15  | 10 mg/m <sup>3</sup> | NE   | 10 mg/m <sup>3</sup> | NE     |
| Methyl Oximino Silane      | 22984-54-9 | 0-5   |                      | None |                      | None   |
| Tetra Oximino Silane       | 34206-40-1 | 0-0.5 |                      | None |                      | None   |
| Toluene                    | 108-88-3   | 0-0.5 | 200 ppm              | NE   | 50 ppm               | 100ppm |
| Vinyl Oximino Silane       | 2224-33-1  | 0-4   |                      | None |                      | None   |
| Aminopropyltriethoxysilane | 919-30-2   | 0-2   |                      | None |                      | None   |

Comments:

Alcohol forms on contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 1000 ppm and ACGIH TLV- skin: TWA 1000 ppm, STEL 1000 ppm.

Methyl ethyl ketoxime is formed upon contact with water or humid air. Provide adequate ventilation to control exposures to within the exposure guideline of 3 ppm (TWA).

### SECTION 3 - EFFECTS OF OVEREXPOSURE

Acute Effects

**Eye:** Direct contact irritates slightly with redness and swelling

**Skin:** Repeated or prolonged contact may cause defatting of the skin leading to dermatitis.  
Product contains oximes which are possible skin sensitizers

**Inhalation:** Vapor overexposure may cause drowsiness, injure blood, liver and may irritate eyes, nose and throat.

**Oral:** Small amounts transferred to the mouth by fingers during use etc. should not injure.  
Swallowing large amounts may injure.

# Novagard Solutions<sup>TM</sup>

## MATERIAL SAFETY DATA SHEET

### SECTION 3 - EFFECTS OF OVEREXPOSURE (continued)

#### Repeated Exposure Effects

- Skin:** None known  
**Inhalation:** Vapor overexposure may cause drowsiness, injure blood, liver and may irritate eyes, nose and throat.  
**Oral:** Small amounts transferred to the mouth by fingers during use etc. should not injure. Swallowing large amounts may injure.

#### Special Hazards

- Carcinogens:** This product does not contain any ingredients listed by IARC, NTP or OSHA as chemical carcinogens.  
**Teratogens:** None known  
**Mutagens:** None known  
**Reproductive Toxins:** None known

### SECTION 4 - FIRST AID MEASURES

- Eyes:** Flush with water for 15 minutes.  
**Skin:** Wipe off and flush with water. Get medical attention if a reaction develops.  
**Inhalation:** Remove to fresh air. Get medical attention if a reaction develops.  
**Oral:** Get immediate medical attention if large amounts are swallowed.

### SECTION 5 - FIRE FIGHTING MEASURES

- Flash Point:** Not Applicable - solid  
**Flammability Limits in Air:** Upper - Not Determined Lower - Not Determined  
**Extinguishing Media:** Water, CO<sub>2</sub>, Dry Chemical, Foam.  
**Special Fire Fighting Procedures:** None known

This product contains Methylpolysiloxanes which can generate formaldehyde at approximately 300° F and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

Disposal of collected product, residues and cleanup materials may be governmentally regulated. Observe all applicable local, state and federal waste management regulations. Scrape up and contain for salvage or disposal. Wash all walking surfaces with detergent and water to reduce slipping hazard. Observe all personal and protection equipment recommendations described in Section 5 and 8. Local, state and federal reporting requirements may apply to spills or releases of this matter into the environment. See applicable regulatory compliance information in Section 15.

# Novagard Solutions™

## MATERIAL SAFETY DATA SHEET

### SECTION 7 - HANDLING AND STORAGE

**Handling:** No special precautions  
**Storage :** Keep container closed and store away from water or moisture.

### SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Engineering Controls

Local exhaust: Recommended    General ventilation: Recommended    Eyewash stations: Recommended

#### Personal Protective Equipment for Routine Handling

**Eye Protection:** Use proper protection - safety glasses as a minimum  
**Skin Protection:** Wash after any contact. Chemical protective gloves are recommended  
**Respiratory Protection:** Not required for properly ventilated areas. If high levels of vapor or mist should accumulate, use NIOSH approved respirator with organic vapor cartridge

#### Personal Protective Equipment for Spills

**Eye Protection:** Avoid eye contact. Use proper protection - safety glasses as a minimum  
**Skin Protection:** Avoid skin contact. Wash after any contact. Chemical protective gloves are recommended  
**Respiratory Protection:** Not required for properly ventilated areas. If high levels of vapor or mist should accumulate, use NIOSH approved respirator with organic vapor cartridge

#### Comments:

Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control exposure within guidelines (see Section 2) or use respiratory protection. Product evolves alcohol when exposed to water or humid air. Provide ventilation during use to control exposure within Section 2 guidelines. Respiratory protection should be considered for exposures resulting from unusual tasks and/or use in non ventilated areas.

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

|                                       |                  |                                    |                |
|---------------------------------------|------------------|------------------------------------|----------------|
| <b>Physical form</b>                  | Grey Paste       | <b>Odor:</b>                       | Slight smell   |
| <b>Specific Gravity @25°C:</b>        | 1.20             | <b>Boiling Point (@ 760 mm Hg)</b> | Not applicable |
| <b>Freezing/melting point</b>         | Not applicable   | <b>Vapor pressure:</b>             | Not applicable |
| <b>Evaporation rate:</b>              | Not applicable   | <b>Volatile content:</b>           | Not applicable |
| <b>Odor threshold</b>                 | 1.0 ppm (acetic) | <b>Percent Volatile by volume:</b> | <8.0           |
| <b>VOC (EPA method 24):</b>           | 31 gm/l          | <b>Evaporation Rate</b>            |                |
| <b>Solubility in water:</b>           | < 1%             | <b>(butyl acetate =1):</b>         | <1.0           |
| <b>Solubility in organic solvent:</b> | Toluene          |                                    |                |

# Novagard Solutions™

## MATERIAL SAFETY DATA SHEET

### SECTION 10 - STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>Chemical stability:</b>   | Stable   |
| <b>Hazardous polymerization:</b>                                   | Will not occur   |
| <b>Conditions to avoid:</b>  | None known   |
| <b>Materials to avoid:</b>   | None known   |
| <b>Conditions to avoid:</b>  | None known   |
| <b>Hazardous thermal decomposition and combustion by-products:</b> | Carbon monoxide, carbon dioxide, silicon dioxide, and formaldehyde |

### SECTION 11 - TOXICOLOGICAL INFORMATION

Methyl ethyl ketoxime produced during cure is toxic. Direct contact with the uncured product may cause irritation of the eyes, nose and throat if contact is repeated or prolonged.

This product and its components are not listed by NTP, IARC or regulated as a carcinogen by OSHA.

### SECTION 12 - ECOLOGICAL INFORMATION

Material will react with water, releasing MEKO which has been determined to be biodegradable and has a static 96 hour LC50 of 48 mg/L (bluegill) and a 48 hour EC50 of 750 mg/L (daphnia)

### SECTION 13 - DISPOSAL CONSIDERATIONS

Unused product is not a RCRA hazardous waste if discarded. Disposal must comply with Federal, State and Local disposal or discharge laws.

The information offered here is for the product as shipped. Use and /or alteration to the product such as mixing with other material may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

### SECTION 14 - TRANSPORTATION INFORMATION

|                    |      |                  |   |      |
|--------------------|------|------------------|---|------|
| DOT shipping name: | None | DOT hazard class | : | None |
| DOT labels:        | None | UN/NA number:    |   | None |
| Placards:          | None | IATA:            |   | None |
| IMO IMDG -code:    | None |                  |   |      |

European Class:

|             |      |
|-------------|------|
| RID (OCTI): | None |
| ADR (ECE):  | None |
| RAR(IATA):  | None |

**Novagard Solutions<sup>TM</sup>**  
**MATERIAL SAFETY DATA SHEET**

SECTION 15 - REGULATORY INFORMATION

**TSCA Status:**

All chemical substances found in this product comply with the Toxic Substances Control act Inventory reporting requirements

**EPA SARA Title III Chemical Listings:**

40 CFR 355 Section 302

Extremely Hazardous Substance List:       None found

Section 312 Hazard Class:

Acute:               Yes

Chronic:           Yes

Fire:               No

Pressure:          No

Reactive :         No

40 CFR 372.65 Section 313

Toxic Chemical List:           Toluene    CAS # 108-88-3

**WHMIS Hazard class:**

D2B Toxic materials

**Hazard Rating System:**

HMIS: Flammability 0, Reactivity 0, Health 2

NFAPA: Flammability 0, Reactivity 0, Health 2

**California Proposition 65:**       Toluene    CAS # 108-88-3

The information presented in this Material Safety Data Sheet relates only to the specific product designated herein, and no warranty, or guarantee, either expressed or implied is made regarding the performance and conditions of this product. This information is based upon information that Novagard believes to be true and accurate; however, it is the responsibility of each user to review this information within the specific context of their intended application.