

Printing date 08/25/2023 Reviewed on 08/25/2023

## 1 Identification

- · Product identifier
- Trade name: NovaFlex QG0 Qwik-Set Glazing Sealant Catalyst (Part B)
- Application of the substance / the mixture Two-part Adhesive and Sealant (Part B)
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
  Novagard Solutions Inc
  5109 Hamilton Avenue

CLEVELAND, OH 44114 USA

- · Information department: R&D Department
- · Emergency telephone number:

CHEMTREC 1-800-424-9300 (USA)

+1 703-741-5970 (International)

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Toxic to Reproduction 1B H360 May damage fertility or the unborn child.



**GHS05 Corrosion** 

Skin Corrosion 1B H314 Causes severe skin burns and eye damage.

Eye Damage 1 H318 Causes serious eye damage.



GHS07

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS05 GHS07

Signal word Danger

· Hazard-determining components of labeling:

N-(3-(trimethoxysilyl)propyl)ethylenediamine dibutyltin dilaurate

· Hazard statements

Causes severe skin burns and eye damage. May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 08/25/2023 Reviewed on 08/25/2023

#### Trade name: NovaFlex QG0 Qwik-Set Glazing Sealant Catalyst (Part B)

(Contd. of page 1)

May damage fertility or the unborn child.

**Precautionary statements** 

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = \*3 Fire = 1 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixture
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

## Dangerous components:

1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine	12–18%
77-58-7	dibutyltin dilaurate	0.5–0.9%

## 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Printing date 08/25/2023 Reviewed on 08/25/2023

Trade name: NovaFlex QG0 Qwik-Set Glazing Sealant Catalyst (Part B)

(Contd. of page 2)

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **5 Fire-fighting measures**

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)

Printing date 08/25/2023 Reviewed on 08/25/2023

Trade name: NovaFlex QG0 Qwik-Set Glazing Sealant Catalyst (Part B)

(Contd. of page 3)

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

### 77-58-7 dibutyltin dilaurate

PEL Long-term value: 0.1 mg/m<sup>3</sup>

as Sn

REL Long-term value: 0.1 mg/m<sup>3</sup>

as Sn, Skin

TLV Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³

as Sn; A4; Skin

- · Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

## · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



#### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material


The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 08/25/2023 Reviewed on 08/25/2023

Trade name: NovaFlex QG0 Qwik-Set Glazing Sealant Catalyst (Part B)

· Eye protection:



(Contd. of page 4)

## 9 Physical and chemical properties

Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Viscous

Color: According to product specification

· Odor: Mild

· Odor threshold: Not determined.

· **pH-value**: Not determined.

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined.

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· **Decomposition temperature:** Not determined.

• **Ignition temperature:** Product is not selfigniting.

• **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

**Lower:** Not determined. **Upper:** Not determined.

· Vapor pressure: Not determined.

Density: Not determined.
Relative density Not determined.
Vapor density Not determined.
Evaporation rate Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

• Other information No further relevant information available.

## 10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 6)

Printing date 08/25/2023 Reviewed on 08/25/2023

Trade name: NovaFlex QG0 Qwik-Set Glazing Sealant Catalyst (Part B)

(Contd. of page 5)

- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Combustion may create carbon monoxide, carbon dioxide, silicone dioxide and formaldehyde

## 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

### 77-58-7 dibutyltin dilaurate

Oral LD50 175 mg/kg (rat)

- Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- Carcinogenic categories
- IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

(Contd. on page 7)

Printing date 08/25/2023 Reviewed on 08/25/2023

Trade name: NovaFlex QG0 Qwik-Set Glazing Sealant Catalyst (Part B)

(Contd. of page 6)

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, IMDG, IATA	UN1760
<u> </u>	
UN proper shipping name DOT	Corrosive liquids, n.o.s. (N-(3-(trimethoxysilyl)prop
DOT	ethylenediamine)
IMDG, IATA	CORROSIVE LIQUID, N.O.S. (N-(3-(trimethoxysil
	propyl)ethylenediamine)
Transport hazard class(es)	
DOT	
<u> </u>	
W. The state of th	
CORROSIVE	
*	
Class	8 Corrosive substances
Label	8
IMDG, IATA	
<u> </u>	
Class	8 Corrosive substances
Label	8
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code):	
EMS Number:	F-A,S-B
Stowage Category	В

Printing date 08/25/2023 Reviewed on 08/25/2023

Trade name: NovaFlex QG0 Qwik-Set Glazing Sealant Catalyst (Part B)

	(Contd. of page 7
· Stowage Code	SW2 Clear of living quarters.
<ul> <li>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</li> </ul>	Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S. (N-(3- (TRIMETHOXYSILYL)PROPYL) ETHYLENEDIAMINE), 8, II

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

- Carlo
· Section 355 (extremely hazardous substances):
58-36-6 Arsenazo III

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):				
63148-62-9	Dimethylpolysiloxane	ACTIVE		
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine	ACTIVE		
68611-44-9	Silica, amorphous	ACTIVE		
77-58-7	dibutyltin dilaurate	ACTIVE		

15396-00-6 (3-isocyanatopropyl)trimethoxysilane ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 9)

Printing date 08/25/2023 Reviewed on 08/25/2023

Trade name: NovaFlex QG0 Qwik-Set Glazing Sealant Catalyst (Part B)

(Contd. of page 8)

### · Carcinogenic categories

#### · EPA (Environmental Protection Agency)

None of the ingredients is listed.

#### TLV (Threshold Limit Value)

77-58-7 dibutyltin dilaurate

A4

### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

### · Hazard pictograms







GHS05 GHS07 GHS08

### · Signal word Danger

### Hazard-determining components of labeling:

N-(3-(trimethoxysilyl)propyl)ethylenediamine dibutyltin dilaurate

#### · Hazard statements

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Regulatory Compliance Department
- · Contact: novagard@novagard.net

(Contd. on page 10)

Printing date 08/25/2023 Reviewed on 08/25/2023

Trade name: NovaFlex QG0 Qwik-Set Glazing Sealant Catalyst (Part B)

(Contd. of page 9)

· Date of preparation / last revision 08/25/2023

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Corrosion 1B: Skin corrosion/irritation - Category 1B Eye Damage 1: Serious eye damage/eye irritation – Category 1

Sensitization - Skin 1: Skin sensitisation - Category 1

Toxic to Reproduction 1B: Reproductive toxicity – Category 1B \* Data compared to the previous version altered.